

View Online at <https://aerobasegroup.com/nsn/5990-00-784-5557>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.5310 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0630 inches

Undercut Diameter:

Between 0.8370 inches and 0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0880 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.2500 inches single shaft

Body Size:

10

Stator Input Voltage Rating In Volts:

2.0

Rotor Input Voltage Rating In Volts:

2.0

Frequency In Hertz:

10000.0

Phase Shift Angle In Deg:

1.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

40.00

Actuator Friction Torque At Minus 55 Deg Celsius:

9.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Alignment Hole Quantity:

3

Pilot Length:

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2810 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0460 inches single shaft

Shaft Slot Width:

0.0460 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.0500 inches

Transformation Ratio:

1.800 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.6780 inches

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800