

View Online at <https://aerobasegroup.com/nsn/5990-00-786-0702>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

Between 2.2550 inches and 2.2850 inches

Flange Diameter:

Between 0.7450 inches and 0.7550 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.7000 inches

Undercut Width:

0.0570 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.6850 inches single shaft and 0.7150 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

31.0 milliamperes

Stator Input Electrical Power Rating:

58.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

640.00

Zso Resistance In Ohms:

93.00

Rotor Dc Resistance In Ohms:

550.00

Stator Dc Resistance In Ohms:

100.00

Phase Shift Angle In Deg:

5.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

20.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Minus 55 Deg Celsius:

9.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.3700 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

1980.00

Shaft Slot Depth:

0.0150 inches single shaft and 0.0350 inches single shaft

Plus J Zso Reactance In Ohms:

350.00

Shaft Slot Width:

0.0150 inches single shaft and 0.0350 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

2.203 rotor to stator

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800