## NSN 5990-00-802-9440

Transmitter Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-802-9440

Body Material:
Steel, corrosion resisting
Body Style:
Standard round c
Shoulder Diameter:
Between 1.3115 inches and 1.3120 inches
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
2.1310 inches
Flange Diameter:
Between 1.4360 inches and 1.4370 inches
Flange Thickness:
0.0930 inches
Undercut Diameter:
1.3120 inches
Undercut Width:
0.0780 inches
Shaft Diameter:
0.1195 inches single shaft and 0.1200 inches single shaft
Shaft Length:
0.5400 inches single shaft
Body Size:
15
Rotor Input Voltage Rating In Volts:
26.0
Frequency In Hertz:
400.0
Rotor Input Current Rating:
65.0 milliamperes
Rotor Input Electrical Power Rating:
330.0 milliwatts
Zro Resistance In Ohms:
80.00
Rotor Dc Resistance In Ohms:
42.00
Stator Dc Resistance In Ohms:
10.80
Phase Shift Angle In Deg:
5.500 input to output
Electrical Error Angular Range In Minutes:
-5.0/+5.0

## NSN 5990-00-802-9440

Transmitter Synchro - Page 2 of 2



Actuator Friction Torque At Minus 55 Deg Celsius:

15.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Alignment Hole Quantity:

4

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

1.5910 inches

**Terminal Location:** 

Rear

Plus J Zro Reactance In Ohms:

400.00

Shaft Slot Depth:

0.0210 inches single shaft and 0.0310 inches single shaft

Shaft Slot Width:

0.0210 inches single shaft and 0.0310 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Alignment Hole Bolt Circle Diameter:

0.8750 inches

**Terminal Type And Quantity:** 

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

## **Demilitarization:**

Yes - demil/mli

Fiig:

A07800