

View Online at <https://aerobasegroup.com/nsn/5990-00-803-0490>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6540 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.8350 inches and 0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0850 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4130 inches single shaft

Body Size:

10

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

80.0 milliamperes

Stator Input Electrical Power Rating:

330.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

78.00

Zso Resistance In Ohms:

44.00

Zrs Resistance In Ohms:

80.00

Rotor Dc Resistance In Ohms:

75.00

Stator Dc Resistance In Ohms:

36.00

Electrical Error Angular Range In Minutes:

-18.0/+18.0

Actuator Friction Torque At Minus 55 Deg Celsius:

30.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

10.0 centimeter-grams

Alignment Hole Quantity:

3

Pilot Length:

0.0380 inches

Shoulder Length:

0.0630 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

136.00

Shaft Slot Depth:

0.0470 inches single shaft

Plus J Zso Reactance In Ohms:

138.00

Shaft Slot Width:

0.0470 inches single shaft

Plus J Zrs Reactance In Ohms:

20.00

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.0620 inches

Transformation Ratio:

1.025 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.6780 inches

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800