

View Online at <https://aerobasegroup.com/nsn/5990-00-812-1439>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round d

Shoulder Diameter:

1.9900 inches

Pilot Diameter:

0.6000 inches

Second Shoulder Diameter:

1.9995 inches

Second Shoulder Length:

0.1700 inches

Overall Length:

4.2990 inches

Flange Diameter:

2.2500 inches

Flange Thickness:

0.2500 inches

Body Diameter:

1.9900 inches

Shaft Diameter:

0.2403 inches single shaft and 0.2405 inches single shaft

Shaft Length:

0.7190 inches single shaft

Maximum Tempurature Rise:

20.0 degrees celsius

Body Size:

23

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

5.7 milliamperes

Stator Input Electrical Power Rating:

50.0 milliwatts

Frequency In Hertz:

500.0

Zso Impedance Magnitude In Ohms:

Between 13400.00 and 16700.00

Zso Impedance Angle In Deg:

Between 81.00 and 84.50

Zrs Impedance Magnitude In Ohms:

Between 1040.00 and 1260.00

Zrs Impedance Angle In Deg:

Between 46.00 and 56.00

Phase Shift Angle In Deg:

2.300 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

20.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

45.00

Electrical Error Angular Range In Minutes:

-3.0/+3.0

Spline Tooth Quantity:

22 single shaft

Pilot Length:

0.0430 inches

Shoulder Length:

0.1700 inches

Aft Of First Flange Diameter:

1.9995 inches

Mounting Surface To Terminal End Distance:

3.5800 inches

Spline Tooth Diametral Pitch:

96 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a

Terminal Location:

Rear

Shaft Thread Length:

0.2900 inches single shaft

Shaft Type:

Spline w/threads single shaft

Transformation Ratio:

0.735 rotor to stator

Shaft Thread Size:

0.250 inches single shaft

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800