

View Online at <https://aerobasegroup.com/nsn/5990-00-813-2254>

**Body Material:**

Steel, stainless

**Body Style:**

Standard round a

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

2.0550 inches

**Flange Diameter:**

0.7500 inches

**Flange Thickness:**

0.0620 inches

**Undercut Diameter:**

0.7000 inches

**Undercut Width:**

0.0570 inches

**Shaft Diameter:**

0.1970 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.4010 inches single shaft and 0.4850 inches single shaft

**Fragility Factor:**

Moderately rugged

**Body Size:**

8

**Rotor Input Voltage Rating In Volts:**

26.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

125.0 milliamperes

**Rotor Input Electrical Power Rating:**

95.0 milliwatts

**Zro Resistance In Ohms:**

60.00

**Zso Resistance In Ohms:**

13.00

**Zrs Resistance In Ohms:**

90.00

**Rotor Dc Resistance In Ohms:**

39.00

**Stator Dc Resistance In Ohms:**

11.40

**Phase Shift Angle In Deg:**

11.500 input to output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

30.00

**Electrical Error Angular Range In Minutes:**

-5.0/+5.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

9.0 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

3.0 centimeter-grams

**Pilot Length:**

0.0430 inches

**Mounting Surface To Terminal End Distance:**

1.3700 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

216.00

**Shaft Slot Depth:**

0.0150 inches single shaft and 0.0350 inches single shaft

**Plus J Zso Reactance In Ohms:**

38.00

**Shaft Slot Width:**

0.0150 inches single shaft and 0.0350 inches single shaft

**Plus J Zrs Reactance In Ohms:**

20.00

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

0.454 rotor to stator

**Terminal Type And Quantity:**

5 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07800