

View Online at <https://aerobasegroup.com/nsn/5990-00-813-9405>

Body Material:

Aluminum

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

1.9750 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0810 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

170.0 milliamperes

Rotor Input Electrical Power Rating:

580.0 milliwatts

Zro Resistance In Ohms:

20.00

Zso Resistance In Ohms:

4.30

Zrs Resistance In Ohms:

25.00

Rotor Dc Resistance In Ohms:

10.50

Stator Dc Resistance In Ohms:

3.60

Phase Shift Angle In Deg:

4.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Torque Gradient Per Angular Deg:

4280.0 millimeter-milligrams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.6000 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

150.00

Plus J Zso Reactance In Ohms:

24.60

Plus J Zrs Reactance In Ohms:

12.20

Shaft Type:

Round single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800