

View Online at <https://aerobasegroup.com/nsn/5990-00-816-1580>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 2.1290 inches and 2.1530 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

Between 0.0900 inches and 0.0960 inches

Undercut Diameter:

Between 0.9700 inches and 0.9800 inches

Undercut Width:

Between 0.0450 inches and 0.0550 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3640 inches single shaft and 0.3880 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

60.0 milliamperes

Stator Input Electrical Power Rating:

600.0 milliwatts

Frequency In Hertz:

400.0

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Receiver Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

Between 0.0590 inches and 0.0650 inches

Shoulder Length:

Between 0.0590 inches and 0.0650 inches

Mounting Surface To Terminal End Distance:

Between 2.0700 inches and 2.0800 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

1.108 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800