

View Online at <https://aerobasegroup.com/nsn/5990-00-818-5235>

**Body Material:**

Aluminum

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.8118 inches and 0.8123 inches

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

1.6540 inches

**Flange Diameter:**

Between 0.9360 inches and 0.9370 inches

**Flange Thickness:**

0.0620 inches

**Undercut Diameter:**

0.8370 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.0895 inches single shaft and 0.0900 inches single shaft

**Shaft Length:**

0.4130 inches single shaft

**Fragility Factor:**

Moderately rugged

**Body Size:**

10

**Rotor Input Voltage Rating In Volts:**

26.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

210.0 milliamperes

**Rotor Input Electrical Power Rating:**

2.0 watts

**Zro Resistance In Ohms:**

35.00

**Zso Resistance In Ohms:**

10.00

**Rotor Dc Resistance In Ohms:**

26.00

**Stator Dc Resistance In Ohms:**

10.90

**Phase Shift Angle In Deg:**

11.000 input to output

**Electrical Error Angular Range In Minutes:**

-7.5/+7.5

**Actuator Friction Torque At Minus 55 Deg Celsius:**

15.0 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

4.0 centimeter-grams

**Alignment Hole Quantity:**

3

**Pilot Length:**

0.0380 inches

**Shoulder Length:**

0.0630 inches

**Mounting Surface To Terminal End Distance:**

1.2410 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

145.00

**Shaft Slot Depth:**

0.0210 inches single shaft and 0.0310 inches single shaft

**Plus J Zso Reactance In Ohms:**

31.00

**Shaft Slot Width:**

0.0210 inches single shaft and 0.0310 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Alignment Hole Depth:**

0.0630 inches

**Alignment Hole Bolt Circle Diameter:**

0.6750 inches

**Terminal Type And Quantity:**

5 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07800