

View Online at <https://aerobasegroup.com/nsn/5990-00-821-6257>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

2.0570 inches

Flange Diameter:

Between 1.0590 inches and 1.0620 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.9620 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

22.0 milliamperes

Stator Input Electrical Power Rating:

150.0 milliwatts

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

17.0 milliamperes

Rotor Input Electrical Power Rating:

100.0 milliwatts

Zro Resistance In Ohms:

315.00

Zso Resistance In Ohms:

280.00

Zrs Resistance In Ohms:

345.00

Rotor Dc Resistance In Ohms:

170.00

Stator Dc Resistance In Ohms:

160.00

Phase Shift Angle In Deg:

6.000 input to output

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

15.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

7.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.6820 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

1500.00

Shaft Slot Depth:

0.0310 inches single shaft

Plus J Zso Reactance In Ohms:

1180.00

Shaft Slot Width:

0.0310 inches single shaft

Plus J Zrs Reactance In Ohms:

1176.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800