

View Online at <https://aerobasegroup.com/nsn/5990-00-825-2882>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round b

Shoulder Diameter:

1.0000 inches

Pilot Diameter:

0.6250 inches

Overall Length:

2.3400 inches

Flange Diameter:

1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

13.0 milliamperes

Stator Input Electrical Power Rating:

75.0 milliwatts

Rotor Input Voltage Rating In Volts:

22.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

14.0 milliamperes

Rotor Input Electrical Power Rating:

59.0 milliwatts

Zro Resistance In Ohms:

450.00

Zso Resistance In Ohms:

300.00

Zrs Resistance In Ohms:

400.00

Rotor Dc Resistance In Ohms:

240.00

Stator Dc Resistance In Ohms:

140.00

Phase Shift Angle In Deg:

5.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 input

Maximum Total Null Voltage Output In Millivolts Per Volt:

75.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.9500 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

1950.00

Plus J Zso Reactance In Ohms:

1550.00

Plus J Zrs Reactance In Ohms:

165.00

Shaft Type:

Round single shaft

Transformation Ratio:

0.685 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800