

View Online at <https://aerobasegroup.com/nsn/5990-00-825-7335>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 2.6030 inches and 2.6270 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches both shafts and 0.1200 inches both shafts

Shaft Length:

0.5520 inches front shaft and 0.5760 inches front shaft

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

136.0 milliamperes

Rotor Input Electrical Power Rating:

450.0 milliwatts

Zro Impedance Magnitude In Ohms:

236.00

Zro Impedance Angle In Deg:

81.00

Zso Impedance Magnitude In Ohms:

40.00

Zso Impedance Angle In Deg:

78.50

Rotor Dc Resistance In Ohms:

19.00

Stator Dc Resistance In Ohms:

5.75

Phase Shift Angle In Deg:

4.700 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

17.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

26.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7650 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches both shafts

Shaft Slot Width:

0.0250 inches both shafts

Shaft Type:

Round, slotted both shafts

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800