

View Online at <https://aerobasegroup.com/nsn/5990-00-827-4891>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

0.6250 inches

Overall Length:

2.2380 inches

Flange Diameter:

1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9800 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3760 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

165.0 milliamperes

Stator Input Electrical Power Rating:

250.0 milliwatts

Frequency In Hertz:

400.0

Zro Impedance Magnitude In Ohms:

418.00

Zro Impedance Angle In Deg:

78.30

Zso Impedance Magnitude In Ohms:

74.30

Zso Impedance Angle In Deg:

79.70

Zrs Impedance Magnitude In Ohms:

104.00

Zrs Impedance Angle In Deg:

26.80

Rotor Dc Resistance In Ohms:

62.10

Stator Dc Resistance In Ohms:

10.00

Phase Shift Angle In Deg:

6.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

40.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Alignment Hole Quantity:

4

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.8620 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1000 inches

Transformation Ratio:

2.203 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.8120 inches

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800