

View Online at <https://aerobasegroup.com/nsn/5990-00-836-7960>

Body Material:

Aluminum

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

2.2100 inches

Flange Diameter:

Between 1.0570 inches and 1.0620 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.9620 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3820 inches single shaft

Maximum Temperature Rise:

50.0 degrees celsius

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

220.0 milliamperes

Rotor Input Electrical Power Rating:

1.1 watts

Zro Resistance In Ohms:

30.00

Rotor Dc Resistance In Ohms:

16.00

Stator Dc Resistance In Ohms:

5.00

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

15.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7660 inches

Terminal Location:

Side

Plus J Zro Reactance In Ohms:

146.00

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800