NSN 5990-00-841-3396

Differential Receiver Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-841-3396 **Body Material:** Steel, stainless **Body Style:** Standard round c **Shoulder Diameter:** Between 0.8118 inches and 0.8123 inches **Pilot Diameter:** Between 0.4995 inches and 0.5000 inches **Overall Length:** 1.6560 inches Flange Diameter: Between 0.9360 inches and 0.9370 inches Flange Thickness: 0.0630 inches **Undercut Diameter:** 0.8400 inches **Undercut Width:** 0.0620 inches **Shaft Diameter:** 0.0895 inches single shaft and 0.0900 inches single shaft **Shaft Length:** 0.3750 inches single shaft **Body Size:** 10 **Stator Input Voltage Rating In Volts:** 26.0 **Stator Input Current Rating:** 32.0 milliamperes **Stator Input Electrical Power Rating:** 220.0 milliwatts Frequency In Hertz: 400.0 **Zro Resistance In Ohms:** 34.00 **Zso Resistance In Ohms:** 212.00 **Zrs Resistance In Ohms:** 44.00

Rotor Dc Resistance In Ohms: 32.00

Stator Dc Resistance In Ohms:

166.00

NSN 5990-00-841-3396

Differential Receiver Synchro - Page 2 of 3



Phase Shift Angle In Deg:
11.600 input to output
Maximum Total Null Voltage Output In Millivolts Per Volt:
40.00
Electrical Error Angular Range In Minutes:
-7.5/+7.5
Actuator Friction Torque At Minus 55 Deg Celsius:
5400.0 millimeter-milligrams
Actuator Friction Torque At Plus 25 Deg Celsius:
2700.0 millimeter-milligrams
Alignment Hole Quantity:
3
Pilot Length:
0.0380 inches
Shoulder Length:
0.0620 inches
Mounting Surface To Terminal End Distance:
1.2810 inches
Terminal Location:
Rear
Plus J Zro Reactance In Ohms:
119.00
Shaft Slot Depth:
0.0310 inches single shaft
Plus J Zso Reactance In Ohms:
783.00
Shaft Slot Width:
0.0270 inches single shaft
Plus J Zrs Reactance In Ohms:
14.00
Shaft Type:
Round, slotted single shaft
Alignment Hole Depth:
0.0500 inches
Alignment Hole Bolt Circle Diameter:
0.6880 inches
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5990-00-841-3396 Differential Receiver Synchro - Page 3 of 3



Fiig:

A07800