

View Online at <https://aerobasegroup.com/nsn/5990-00-844-5659>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.7230 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0630 inches

Undercut Diameter:

Between 0.8370 inches and 0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4750 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

10

Stator Input Voltage Rating In Volts:

10.2

Stator Input Current Rating:

17.0 milliamperes

Stator Input Electrical Power Rating:

54.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

685.00

Zso Resistance In Ohms:

180.00

Zrs Resistance In Ohms:

1000.00

Rotor Dc Resistance In Ohms:

466.00

Stator Dc Resistance In Ohms:

175.00

Phase Shift Angle In Deg:

12.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

50.00

Electrical Error Angular Range In Minutes:

-7.5/+7.5

Alignment Hole Quantity:

2

Pilot Length:

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2480 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

2700.00

Plus J Zso Reactance In Ohms:

560.00

Plus J Zrs Reactance In Ohms:

425.00

Shaft Type:

Round single shaft

Alignment Hole Bolt Circle Diameter:

0.6780 inches

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800