

View Online at <https://aerobasegroup.com/nsn/5990-00-847-1164>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6540 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.8350 inches and 0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4130 inches single shaft

Body Size:

10

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

55.0 milliamperes

Rotor Input Electrical Power Rating:

600.0 milliwatts

Zro Resistance In Ohms:

268.00

Zso Resistance In Ohms:

65.00

Zrs Resistance In Ohms:

342.00

Rotor Dc Resistance In Ohms:

200.00

Stator Dc Resistance In Ohms:

42.00

Transformation Ratio Equality In Percent:

3.0

Phase Shift Angle In Deg:

17.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

60.00

Electrical Error Angular Range In Minutes:

-18.0/+18.0

Actuator Friction Torque At Minus 55 Deg Celsius:

25.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

7.00 centimeter-grams

Alignment Hole Quantity:

4

Pilot Length:

0.0380 inches

Shoulder Length:

0.0630 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

620.00

Shaft Slot Depth:

0.0160 inches single shaft and 0.0310 inches single shaft

Plus J Zso Reactance In Ohms:

188.00

Shaft Slot Width:

0.0270 inches single shaft

Plus J Zrs Reactance In Ohms:

118.00

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.0630 inches

Transformation Ratio:

0.454 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.6780 inches

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800