NSN 5990-00-847-3806

Control Transformer Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-847-3806

Body Material:

Steel, stainless

Body Style:

Standard round d

Shoulder Diameter:

Between 1.9850 inches and 1.9900 inches

Pilot Diameter:

Between 0.5900 inches and 0.6000 inches

Second Shoulder Diameter:

Between 1.9985 inches and 1.9995 inches

Second Shoulder Length:

Between 0.1680 inches and 0.1700 inches

Overall Length:

4.2940 inches

Flange Diameter:

Between 2.2490 inches and 2.2500 inches

Flange Thickness:

Between 0.2480 inches and 0.2500 inches

Body Diameter:

Between 1.9850 inches and 1.9900 inches

Shaft Diameter:

0.2402 inches single shaft and 0.2405 inches single shaft

Shaft Length:

0.7190 inches single shaft

Fragility Factor:

Moderately rugged

Maximum Tempurature Rise:

45.0 degrees celsius

Body Size:

23

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

20.0 milliamperes

Stator Input Electrical Power Rating:

500.0 milliwatts

Frequency In Hertz:

60.0

Zro Resistance In Ohms:

1015.00

Zso Resistance In Ohms:

492.00

NSN 5990-00-847-3806

Control Transformer Synchro - Page 2 of 3



Zrs Resistance In Ohms: 239.00 Maximum Fundamental Null Voltage In Millivolts Per Volt: 60.00 output Maximum Total Null Voltage Output In Millivolts Per Volt: 75.00 **Electrical Error Angular Range In Minutes:** -6.0/+6.0 **Spline Tooth Quantity:** 22 single shaft **Actuator Friction Torque At Minus 55 Deg Celsius:** 0.50 inch-ounces **Actuator Friction Torque At Plus 25 Deg Celsius:** 0.20 inch-ounces **Alignment Hole Quantity:** Pilot Length: Between 0.0360 inches and 0.0460 inches **Shoulder Length:** 0.2500 inches Aft Of First Flange Diameter: Between 1.9985 inches and 1.9995 inches **Mounting Surface To Terminal End Distance:** 3.4450 inches **Spline Tooth Diametral Pitch:** 96 single shaft **Shaft Thread Series Designator:** Unf single shaft **Shaft Thread Direction:** Right-hand single shaft **Shaft Thread Class:** 2a **Terminal Location:** Rear **Shaft Thread Length:** 0.2660 inches single shaft Plus J Zro Reactance In Ohms: 2746.00 Plus J Zso Reactance In Ohms: 4027.00

Shaft Type:

81.00

Spline w/threads single shaft

Plus J Zrs Reactance In Ohms:

NSN 5990-00-847-3806 Control Transformer Synchro - Page 3 of 3



lignment Hole Depth:
.1250 inches
ransformation Ratio:
.735 rotor to stator
lignment Hole Bolt Circle Diameter:
.6420 inches
Shaft Thread Size:
.250 inches single shaft
est Data Document:
1349-mil-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
nvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
erminal Type And Quantity:
screw
Specification Data:
1349-mil-s-20708/94 government specification
Shelf Life:
I/a
Init Of Measure:
Demilitarization:
'es - demil/mli
iig:
.07800