

View Online at <https://aerobasegroup.com/nsn/5990-00-850-8206>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.1610 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.3670 inches single shaft

Shaft Length:

0.3670 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

86.0 milliamperes

Stator Input Electrical Power Rating:

90.0 milliwatts

Frequency In Hertz:

400.0

Zso Impedance Magnitude In Ohms:

135.00

Zso Impedance Angle In Deg:

80.00

Phase Shift Angle In Deg:

4.000 output to input

Maximum Fundamental Null Voltage In Millivolts Per Volt:

20.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Alignment Hole Quantity:

4

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7940 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0300 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.0990 inches

Transformation Ratio:

2.203 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.8120 inches

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800