## NSN 5990-00-851-2793

Differential Transmitter Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-851-2793

**Body Material:** Steel, stainless **Body Style:** Standard round d **Shoulder Diameter:** Between 1.9850 inches and 1.9900 inches **Pilot Diameter:** Between 0.5900 inches and 0.6000 inches **Second Shoulder Diameter:** Between 1.9985 inches and 1.9995 inches **Second Shoulder Length:** Between 0.1680 inches and 0.1700 inches **Overall Length:** 4.2940 inches Flange Diameter: Between 2.2490 inches and 2.2500 inches Flange Thickness: **Body Diameter:** 

Between 0.2480 inches and 0.2500 inches

Between 1.9850 inches and 1.9900 inches

**Shaft Diameter:** 

0.2402 inches single shaft and 0.2405 inches single shaft

**Shaft Length:** 

0.6930 inches single shaft and 0.7190 inches single shaft

**Fragility Factor:** 

Moderately rugged

**Maximum Tempurature Rise:** 

45.0 degrees celsius

**Body Size:** 

23

**Stator Input Voltage Rating In Volts:** 

**Stator Input Current Rating:** 

75.0 milliamperes

**Stator Input Electrical Power Rating:** 

1.6 watts

Frequency In Hertz:

60.0

**Zro Resistance In Ohms:** 

236.00

**Zso Resistance In Ohms:** 

217.00

## NSN 5990-00-851-2793

Differential Transmitter Synchro - Page 2 of 3



Zrs Resistance In Ohms:  485.00  Zso-9 Designator Resistance In Ohms:  206.00  Maximum Fundamental Null Voltage In Millivolts Per Volt:  75.00 output  Maximum Total Null Voltage Output In Millivolts Per Volt:  100.00  Electrical Error Angular Range In Minutes:  -8.0/+8.0  Actuator Friction Torque At Minus 55 Deg Celsius:  0.50 inch-ounces
Zso-9 Designator Resistance In Ohms: 206.00  Maximum Fundamental Null Voltage In Millivolts Per Volt: 75.00 output  Maximum Total Null Voltage Output In Millivolts Per Volt: 100.00  Electrical Error Angular Range In Minutes: -8.0/+8.0  Actuator Friction Torque At Minus 55 Deg Celsius:
206.00  Maximum Fundamental Null Voltage In Millivolts Per Volt: 75.00 output  Maximum Total Null Voltage Output In Millivolts Per Volt: 100.00  Electrical Error Angular Range In Minutes: -8.0/+8.0  Actuator Friction Torque At Minus 55 Deg Celsius:
Maximum Fundamental Null Voltage In Millivolts Per Volt: 75.00 output  Maximum Total Null Voltage Output In Millivolts Per Volt: 100.00  Electrical Error Angular Range In Minutes: -8.0/+8.0  Actuator Friction Torque At Minus 55 Deg Celsius:
75.00 output  Maximum Total Null Voltage Output In Millivolts Per Volt: 100.00  Electrical Error Angular Range In Minutes: -8.0/+8.0  Actuator Friction Torque At Minus 55 Deg Celsius:
Maximum Total Null Voltage Output In Millivolts Per Volt: 100.00  Electrical Error Angular Range In Minutes: -8.0/+8.0  Actuator Friction Torque At Minus 55 Deg Celsius:
100.00  Electrical Error Angular Range In Minutes: -8.0/+8.0  Actuator Friction Torque At Minus 55 Deg Celsius:
Electrical Error Angular Range In Minutes: -8.0/+8.0  Actuator Friction Torque At Minus 55 Deg Celsius:
-8.0/+8.0  Actuator Friction Torque At Minus 55 Deg Celsius:
Actuator Friction Torque At Minus 55 Deg Celsius:
0.50 inch-ounces
0.00 III0IT0UII063
Actuator Friction Torque At Plus 25 Deg Celsius:
0.20 inch-ounces
Alignment Hole Quantity:
3
Pilot Length:
Between 0.0360 inches and 0.0460 inches
Shoulder Length:
0.2500 inches
Aft Of First Flange Diameter:
Between 1.9985 inches and 1.9995 inches
Mounting Surface To Terminal End Distance:
3.4450 inches
Shaft Thread Series Designator:
Unf single shaft
Shaft Thread Direction:
Right-hand single shaft
Shaft Thread Class:
2a
Terminal Location:
Rear
Shaft Thread Length:
0.3100 inches single shaft and 0.3300 inches single shaft
Plus J Zro Reactance In Ohms:
1590.00
Plus J Zso Reactance In Ohms:
796.00
Plus J Zrs Reactance In Ohms:
167.00
Shaft Type:
Round, threaded single shaft

0.1250 inches

**Alignment Hole Depth:** 

NSN 5990-00-851-2793 Differential Transmitter Synchro - Page 3 of 3



Transformation Ratio:
0.783 rotor to stator
Alignment Hole Bolt Circle Diameter:
1.6420 inches
Plus J Zso-9 Designator Reactance In Ohms:
271.00
Shaft Thread Size:
0.2500 inches single shaft
Special Features:
Slotted keyway full length of shaft
Test Data Document:
31349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Ferminal Type And Quantity:
5 screw
Specification Data:
31349-mil-s-20708/94 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A07800