

View Online at <https://aerobasegroup.com/nsn/5990-00-852-0432>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.2370 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

165.0 milliamperes

Stator Input Electrical Power Rating:

800.0 milliwatts

Frequency In Hertz:

400.0

Zro Impedance Magnitude In Ohms:

218.00

Zro Impedance Angle In Deg:

81.00

Zso Impedance Magnitude In Ohms:

37.50

Zso Impedance Angle In Deg:

80.70

Phase Shift Angle In Deg:

6.500 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

20.00

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Minus 55 Deg Celsius:

15.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Alignment Hole Quantity:

4

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7960 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.454 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.8120 inches

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800