

View Online at <https://aerobasegroup.com/nsn/5990-00-855-7291>

Body Material:

Aluminum alloy

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

0.5000 inches

Overall Length:

1.7190 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.8370 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4690 inches single shaft

Body Size:

10

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

115.00

Zso Resistance In Ohms:

31.70

Zrs Resistance In Ohms:

152.00

Phase Shift Angle In Deg:

10.800 input to output

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

15.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

5.00 centimeter-grams

Pilot Length:

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2500 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

410.00

Shaft Slot Depth:

0.0210 inches single shaft and 0.0310 inches single shaft

Plus J Zso Reactance In Ohms:

110.00

Shaft Slot Width:

0.0200 inches single shaft and 0.0300 inches single shaft

Plus J Zrs Reactance In Ohms:

67.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800