NSN 5990-00-866-3694

Transmitter Synchro - Page 1 of 2

Between 0.8118 inches and 0.8123 inches

Body Material:

Aluminum

Body Style:

Standard round c

Shoulder Diameter:



View Online at https://aerobasegroup.com/nsn/5990-00-866-3694

Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
1.6560 inches
Flange Diameter:
Between 0.9360 inches and 0.9370 inches
Flange Thickness:
0.0630 inches
Undercut Diameter:
Between 0.8370 inches and 0.8400 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
0.0895 inches single shaft and 0.0900 inches single shaft
Shaft Length:
0.3750 inches single shaft
Body Size:
10
Rotor Input Voltage Rating In Volts:
26.0
Frequency In Hertz:
400.0
Rotor Input Current Rating:
55.0 milliamperes
Rotor Input Electrical Power Rating:
700.0 milliwatts
Zro Resistance In Ohms:
270.00
Zso Resistance In Ohms:
43.00
Zrs Resistance In Ohms:
Between 240.00 and 396.00
Phase Shift Angle In Deg:
18.000 input to output
Electrical Error Angular Range In Minutes:
-18.0/+18.0

NSN 5990-00-866-3694 Transmitter Synchro - Page 2 of 2



Actuator Friction Torque At Minus 55 Deg Celsius:
15.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
5.0 centimeter-grams
Alignment Hole Quantity:
3
Pilot Length:
0.0380 inches
Shoulder Length:
0.0620 inches
Mounting Surface To Terminal End Distance:
1.2810 inches
Terminal Location:
Rear
Plus J Zro Reactance In Ohms:
670.00
Shaft Slot Depth:
0.0200 inches single shaft and 0.0350 inches single shaft
Plus J Zso Reactance In Ohms:
170.00
Shaft Slot Width:
0.0150 inches single shaft and 0.0300 inches single shaft
Plus J Zrs Reactance In Ohms:
Between 59.00 and 120.00
Shaft Type:
Round, slotted single shaft
Alignment Hole Depth:
0.0500 inches
Alignment Hole Bolt Circle Diameter:
0.6780 inches
Terminal Type And Quantity:
7 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800