

View Online at <https://aerobasegroup.com/nsn/5990-00-872-9370>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.0280 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

Between 0.0900 inches and 0.0960 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.2110 inches single shaft and 0.2290 inches single shaft

Maximum Temperature Rise:

7.0 degrees celsius

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

136.0 milliamperes

Rotor Input Electrical Power Rating:

450.0 milliwatts

Zro Resistance In Ohms:

37.00

Zso Resistance In Ohms:

8.00

Rotor Dc Resistance In Ohms:

19.00

Stator Dc Resistance In Ohms:

5.75

Phase Shift Angle In Deg:

4.700 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

26.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

46.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

Between 0.0590 inches and 0.0650 inches

Shoulder Length:

Between 0.0590 inches and 0.0650 inches

Mounting Surface To Terminal End Distance:

1.7990 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

233.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

39.00

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800