

View Online at <https://aerobasegroup.com/nsn/5990-00-877-9838>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6420 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3520 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

7.0 milliamperes

Stator Input Electrical Power Rating:

30.0 milliwatts

Frequency In Hertz:

400.0

Zso Resistance In Ohms:

610.00

Phase Shift Angle In Deg:

14.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

25.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

40.00

Electrical Error Angular Range In Minutes:

-8.0/+8.0

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2900 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

1565.00

Shaft Slot Width:

0.0170 inches single shaft and 0.0320 inches single shaft

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800