

View Online at <https://aerobasegroup.com/nsn/5990-00-879-4301>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4950 inches and 0.5000 inches

Overall Length:

1.6150 inches

Flange Diameter:

Between 0.7470 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0850 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

120.0 milliamperes

Rotor Input Electrical Power Rating:

720.0 milliwatts

Zro Resistance In Ohms:

50.00

Zrs Resistance In Ohms:

75.00

Phase Shift Angle In Deg:

10.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

20.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

9.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

Between 0.0400 inches and 0.0430 inches

Mounting Surface To Terminal End Distance:

1.2400 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

210.00

Shaft Slot Depth:

0.0310 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

20.00

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800