

View Online at <https://aerobasegroup.com/nsn/5990-00-879-8016>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 2.3170 inches and 2.3410 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.5520 inches single shaft and 0.5760 inches single shaft

Maximum Temperature Rise:

0.5 degrees celsius

Body Size:

11

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

21.0 milliamperes

Stator Input Electrical Power Rating:

30.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

3340.00

Zso Resistance In Ohms:

577.00

Rotor Dc Resistance In Ohms:

385.00

Stator Dc Resistance In Ohms:

60.00

Phase Shift Angle In Deg:

4.200 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

34.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

53.00

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7650 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

79.20

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

80.70

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

2.203 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800