

View Online at <https://aerobasegroup.com/nsn/5990-00-881-6624>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.8080 inches

Flange Diameter:

Between 0.9270 inches and 0.9400 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.5620 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

23.1 milliamperes

Stator Input Electrical Power Rating:

60.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

800.00

Zso Resistance In Ohms:

115.00

Rotor Dc Resistance In Ohms:

23.50

Stator Dc Resistance In Ohms:

560.00

Phase Shift Angle In Deg:

14.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

40.00

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Minus 55 Deg Celsius:

8.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Alignment Hole Quantity:

3

Pilot Length:

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2080 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

2900.00

Shaft Slot Depth:

0.0310 inches single shaft

Plus J Zso Reactance In Ohms:

470.00

Shaft Slot Width:

0.0310 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.0500 inches

Alignment Hole Bolt Circle Diameter:

0.6780 inches

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800