

View Online at <https://aerobasegroup.com/nsn/5990-00-888-0718>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.9500 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

Between 0.0580 inches and 0.0650 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

0.0570 inches

Shaft Diameter:

0.1180 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3800 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

50.0 milliamperes

Rotor Input Electrical Power Rating:

390.0 milliwatts

Zro Resistance In Ohms:

190.00

Zso Resistance In Ohms:

30.00

Rotor Dc Resistance In Ohms:

150.00

Stator Dc Resistance In Ohms:

25.00

Transformation Ratio Equality In Percent:

0.2

Phase Shift Angle In Deg:

20.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

20.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Interaxis Error Angular Range In Minutes:

-5.0/+5.0

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Minus 55 Deg Celsius:

9.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.00 centimeter-grams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.3700 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

560.00

Shaft Slot Depth:

0.0250 inches single shaft

Plus J Zso Reactance In Ohms:

135.00

Shaft Slot Width:

0.0200 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

7 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800