

View Online at <https://aerobasegroup.com/nsn/5990-00-891-4085>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

0.5000 inches

Overall Length:

1.8150 inches

Flange Diameter:

0.7500 inches

Flange Thickness:

0.0670 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

0.0570 inches

Shaft Diameter:

0.0900 inches single shaft

Shaft Length:

0.4670 inches single shaft

Schematic Diagram Designator:

Err-090

Fragility Factor:

Moderately rugged

End Application:

6610-00-931-3658

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

87.0 milliamperes

Stator Input Electrical Power Rating:

260.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

210.00

Zso Resistance In Ohms:

28.00

Zrs Resistance In Ohms:

250.00

Rotor Dc Resistance In Ohms:

143.00

Stator Dc Resistance In Ohms:

30.00

Phase Shift Angle In Deg:

9.000 output to input

Maximum Total Null Voltage Output In Millivolts Per Volt:

25.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

9.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Shaft Radial Play Test Point:

0.125 inches

Shaft Maximum Radial Play:

0.0008 inches

Shaft End Play:

0.0015 inches

Pilot Length:

0.0480 centimeters

Mounting Surface To Terminal End Distance:

1.3000 inches

Shaft Maximum Runout:

0.0010 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

690.00

Plus J Zso Reactance In Ohms:

114.00

Plus J Zrs Reactance In Ohms:

73.00

Shaft Type:

Round single shaft

Shaft Radial Play Determining Weight:

4.0 ounces

Shaft End Play Determining Weight:

8.0 ounces

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800