

View Online at <https://aerobasegroup.com/nsn/5990-00-891-5370>

**Body Material:**

Steel, corrosion resisting

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.9700 inches and 0.9750 inches

**Pilot Diameter:**

Between 0.6245 inches and 0.6250 inches

**Overall Length:**

2.3270 inches

**Flange Diameter:**

Between 1.0590 inches and 1.0620 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

Between 0.9995 inches and 1.0000 inches

**Undercut Width:**

0.0500 inches

**Shaft Diameter:**

0.1870 inches single shaft and 0.1873 inches single shaft

**Shaft Length:**

0.5550 inches single shaft

**Body Size:**

11

**Stator Input Voltage Rating In Volts:**

90.0

**Stator Input Current Rating:**

20.0 milliamperes

**Stator Input Electrical Power Rating:**

300.0 milliwatts

**Frequency In Hertz:**

400.0

**Phase Shift Angle In Deg:**

7.500 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

30.00 output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

60.00

**Electrical Error Angular Range In Minutes:**

-7.0/+7.0

**Actuator Friction Torque At Plus 25 Deg Celsius:**

0.05 inch-ounces

**Alignment Hole Quantity:**

4

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.7720 inches

**Terminal Location:**

Rear

**Shaft Type:**

Round single shaft

**Alignment Hole Depth:**

0.1250 inches

**Transformation Ratio:**

0.735 rotor to stator

**Alignment Hole Bolt Circle Diameter:**

0.8120 inches

**Terminal Type And Quantity:**

5 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07800