

View Online at <https://aerobasegroup.com/nsn/5990-00-891-5370>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9700 inches and 0.9750 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.3270 inches

Flange Diameter:

Between 1.0590 inches and 1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

Between 0.9995 inches and 1.0000 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1870 inches single shaft and 0.1873 inches single shaft

Shaft Length:

0.5550 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

20.0 milliamperes

Stator Input Electrical Power Rating:

300.0 milliwatts

Frequency In Hertz:

400.0

Phase Shift Angle In Deg:

7.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

60.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Plus 25 Deg Celsius:

0.05 inch-ounces

Alignment Hole Quantity:

4

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7720 inches

Terminal Location:

Rear

Shaft Type:

Round single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.735 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.8120 inches

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800