

View Online at <https://aerobasegroup.com/nsn/5990-00-898-1398>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.7560 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0900 inches single shaft

Shaft Length:

0.5150 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

30.0 milliamperes

Stator Input Electrical Power Rating:

96.0 milliwatts

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

14.3 milliamperes

Rotor Input Electrical Power Rating:

114.0 milliwatts

Zro Resistance In Ohms:

109.00

Zso Resistance In Ohms:

560.00

Zrs Resistance In Ohms:

154.00

Rotor Dc Resistance In Ohms:

98.00

Stator Dc Resistance In Ohms:

377.00

Phase Shift Angle In Deg:

10.300 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

0.2410 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

362.00

Shaft Slot Depth:

0.0200 inches single shaft

Plus J Zso Reactance In Ohms:

1900.00

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

54.50

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.446 rotor to stator

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800