

View Online at <https://aerobasegroup.com/nsn/5990-00-900-4126>

**Body Material:**

Steel, corrosion resisting

**Body Style:**

Standard round c

**Shoulder Diameter:**

0.8123 inches

**Pilot Diameter:**

0.5000 inches

**Overall Length:**

1.5460 inches

**Flange Diameter:**

0.9370 inches

**Flange Thickness:**

0.0620 inches

**Undercut Diameter:**

0.8400 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.0900 inches single shaft

**Shaft Length:**

0.2500 inches single shaft

**Body Size:**

10

**Stator Input Voltage Rating In Volts:**

26.0

**Stator Input Current Rating:**

32.0 milliamperes

**Stator Input Electrical Power Rating:**

220.0 milliwatts

**Frequency In Hertz:**

400.0

**Zro Resistance In Ohms:**

250.00

**Zso Resistance In Ohms:**

212.00

**Zrs Resistance In Ohms:**

320.00

**Phase Shift Angle In Deg:**

11.600 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

1.00 output

**Electrical Error Angular Range In Minutes:**

-15.0/+15.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

9.00 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

3.00 centimeter-grams

**Pilot Length:**

0.0380 inches

**Shoulder Length:**

0.1250 inches

**Mounting Surface To Terminal End Distance:**

1.2810 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

630.00

**Shaft Slot Depth:**

0.0470 inches single shaft

**Plus J Zso Reactance In Ohms:**

783.00

**Shaft Slot Width:**

0.0470 inches single shaft

**Plus J Zrs Reactance In Ohms:**

70.00

**Shaft Type:**

Round, slotted single shaft

**Terminal Type And Quantity:**

7 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07800