

NSN 5990-00-904-3314 Receiver-transmitter Synchro - Page 1 of 3 View Online at https://aerobasegroup.com/nsn/5990-00-904-3314 **Body Material:** Steel, stainless **Body Style:** Standard round d **Shoulder Diameter:** Between 1.9850 inches and 1.9900 inches **Pilot Diameter:** 0.5950 inches **Second Shoulder Diameter:** Between 1.9985 inches and 1.9995 inches **Second Shoulder Length:** 0.1700 inches **Overall Length:** 4.2990 inches Flange Diameter: Between 2.2490 inches and 2.2500 inches Flange Thickness: 0.2500 inches **Body Diameter:** 1.9900 inches **Shaft Diameter:** 0.2403 inches single shaft and 0.2405 inches single shaft

Shaft Length:

0.7190 inches single shaft

Fragility Factor:

Moderately rugged

Maximum Tempurature Rise:

30.0 degrees celsius

Body Size:

23

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

720.0 milliamperes

Zss Impedance Magnitude In Ohms:

Between 6.50 and 8.10

Zss Impedance Angle In Deg:

Between 42.00 and 46.00

Phase Shift Angle In Deg:

2.000 input to output

NSN 5990-00-904-3314

Receiver-transmitter Synchro - Page 2 of 3



Maximum Fundamental Null Voltage In Millivolts Per Volt:
30.00 output
Maximum Total Null Voltage Output In Millivolts Per Volt:
150.00
Electrical Error Angular Range In Minutes:
6.0/+6.0
Spline Tooth Quantity:
21 single shaft
Receiver Error Angular Range In Minutes:
45.0/+45.0
Torque Gradient Per Angular Deg:
0.250 inch-ounces
Pilot Length:
0.0430 inches
Shoulder Length:
0.2500 inches
Aft Of First Flange Diameter:
Between 1.9985 inches and 1.9995 inches
Mounting Surface To Terminal End Distance:
3.5800 inches
Spline Tooth Diametral Pitch:
96 single shaft
Shaft Thread Series Designator:
Unf single shaft
Shaft Thread Direction:
Right-hand single shaft
Shaft Thread Class:
2a single shaft
Ferminal Location:
Rear
Shaft Thread Length:
0.2900 inches single shaft
Shaft Type:
Spline w/threads single shaft
Transformation Ratio:
0.783 rotor to stator
Shaft Thread Size:
0.250 inches single shaft
Test Data Document:
31349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
\sim .

Terminal Type And Quantity:

5 screw

Specification Data:

NSN 5990-00-904-3314

Receiver-transmitter Synchro - Page 3 of 3



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800