

View Online at <https://aerobasegroup.com/nsn/5990-00-905-0638>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6590 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.4180 inches single shaft

Shaft Length:

0.4180 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

30.0 milliamperes

Stator Input Electrical Power Rating:

23.0 milliwatts

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

38.0 milliamperes

Rotor Input Electrical Power Rating:

39.0 milliwatts

Rotor Dc Resistance In Ohms:

230.00

Stator Dc Resistance In Ohms:

170.00

Phase Shift Angle In Deg:

20.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0250 inches single shaft

Shaft Slot Width:

0.0200 inches single shaft

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800