

View Online at <https://aerobasegroup.com/nsn/5990-00-905-1516>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.7430 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0430 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

15.0

Stator Input Current Rating:

30.0 milliamperes

Stator Input Electrical Power Rating:

192.0 milliwatts

Frequency In Hertz:

400.0

Rotor Dc Resistance In Ohms:

200.00

Stator Dc Resistance In Ohms:

200.00

Compensation Method:

Winding compensated

Compensator Dc Resistance In Ohms:

210.00

Phase Shift Angle In Deg:

22.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

75.00

Interaxis Error Angular Range In Minutes:

-5.0/+5.0

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.3680 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0250 inches single shaft

Shaft Slot Width:

0.0200 inches single shaft

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800