NSN 5990-00-905-1836

Transmitter Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-905-1836

Body Material: Steel, corrosion resisting **Body Style:** Standard round c Shoulder Diameter: Between 1.3070 inches and 1.3120 inches **Pilot Diameter:** Between 0.8745 inches and 0.8750 inches **Overall Length:** 2.3120 inches Flange Diameter: Between 1.4320 inches and 1.4370 inches Flange Thickness: 0.0930 inches **Undercut Diameter:** 1.3120 inches **Undercut Width:** 0.0780 inches Shaft Diameter: 0.1872 inches single shaft Shaft Length: 0.5400 inches single shaft **Fragility Factor:** Moderately rugged Maximum Tempurature Rise: 20.0 degrees celsius **Body Size:** 15 **Rotor Input Voltage Rating In Volts:** 115.0 **Frequency In Hertz:** 400.0 **Rotor Input Current Rating:** 85.0 milliamperes **Rotor Input Electrical Power Rating:** 1.0 watts Zro Impedance Magnitude In Ohms: Between 1402.00 and 1643.00 Zro Impedance Angle In Deg: Between 81.40 and 84.60 **Zss Impedance Magnitude In Ohms:** Between 123.00 and 138.00

NSN 5990-00-905-1836

Transmitter Synchro - Page 2 of 3



Zss Impedance Angle In Deg:
Between 26.50 and 31.50
Phase Shift Angle In Deg:
4.000 input to output
Maximum Fundamental Null Voltage In Millivolts Per Volt:
32.00 output
Maximum Total Null Voltage Output In Millivolts Per Volt:
60.00
Electrical Error Angular Range In Minutes:
-6.0/+6.0
Spline Tooth Quantity:
21 single shaft
Actuator Friction Torque At Plus 25 Deg Celsius:
0.05 inch-ounces
Pilot Length:
0.0400 inches
Shoulder Length:
0.1320 inches
Mounting Surface To Terminal End Distance:
1.7720 inches
Spline Tooth Diametral Pitch:
120 single shaft
Shaft Thread Series Designator:
Unf single shaft
Shaft Thread Direction:
Right-hand single shaft
Shaft Thread Class:
2a single shaft
Terminal Location:
Rear
Shaft Thread Length:
0.1850 inches single shaft
Shaft Type:
Spline w/threads single shaft
Transformation Ratio:
0.783 rotor to stator
Shaft Thread Size:
0.190 inches single shaft
Test Data Document:
81349-mil-s-20708 specification (includes engineering type bul

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 screw

Specification Data:

NSN 5990-00-905-1836

Transmitter Synchro - Page 3 of 3

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800

