## NSN 5990-00-911-6672



T '' O I D 4 (O
Transmitter Synchro - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5990-00-911-6672
Body Material:
Steel, corrosion resisting
Body Style:
Standard round double flange b
Shoulder Diameter:
Between 3.6230 inches and 3.6250 inches
Pilot Diameter:
1.6300 inches
Overall Length:
6.0500 inches
Flange Diameter:
3.3750 inches
Flange Thickness:
Between 0.2450 inches and 0.2500 inches
Shaft Diameter:
0.2498 inches single shaft and 0.2500 inches single shaft
Shaft Length:
0.7600 inches single shaft and 0.7800 inches single shaft
Fragility Factor:
Moderately rugged
Distance Between Flanges:
Between 1.8070 inches and 1.8170 inches
Body Size:
34
Rotor Input Voltage Rating In Volts:
115.0
Frequency In Hertz:
60.0
Rotor Input Current Rating:
1.5 amperes
Rotor Input Electrical Power Rating:
21.0 watts microwatts

**Electrical Error Angular Range In Minutes:** 

-9.0/+9.0

**Torque Gradient Per Angular Deg:** 

0.480 inch-ounces

**Shaft Radial Play Test Point:** 

0.125 inches

**Shaft Maximum Radial Play:** 

0.0005 inches

**Shaft End Play:** 

0.0080 inches

## **NSN 5990-00-911-6672** Transmitter Synchro - Page 2 of 2



Pilot Length:
0.0620 inches
Shoulder Length:
1.2420 centimeters
Shaft Maximum Runout:
0.0005 inches
Shaft Thread Series Designator:
Unf single shaft
Shaft Thread Direction:
Right-hand single shaft
Shaft Thread Class:
2a single shaft
Terminal Location:
Rear
Shaft Thread Length:
0.1870 inches single shaft
Shaft Type:
Round, threaded single shaft
Shaft Thread Size:
0.250 inches single shaft
Shaft Radial Play Determining Weight:
24.0 ounces
Shaft End Play Determining Weight:
48.0 ounces
Terminal Type And Quantity:
5 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800