

View Online at <https://aerobasegroup.com/nsn/5990-00-912-2193>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

0.9750 inches

Pilot Diameter:

0.6250 inches

Overall Length:

2.4700 inches

Flange Diameter:

1.0620 inches

Flange Thickness:

0.0990 inches

Undercut Diameter:

1.0000 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.5000 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

20.0 milliamperes

Stator Input Electrical Power Rating:

250.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

632.00

Zso Resistance In Ohms:

863.00

Zrs Resistance In Ohms:

564.00

Rotor Dc Resistance In Ohms:

385.00

Stator Dc Resistance In Ohms:

555.00

Phase Shift Angle In Deg:

4.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

59.00 input

Maximum Total Null Voltage Output In Millivolts Per Volt:

94.00

Electrical Error Angular Range In Minutes:

-6.0/+6.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7200 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

3350.00

Plus J Zso Reactance In Ohms:

5560.00

Plus J Zrs Reactance In Ohms:

290.00

Shaft Type:

Round single shaft

Transformation Ratio:

0.735 rotor to stator

Terminal Type And Quantity:

5 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800