

View Online at <https://aerobasegroup.com/nsn/5990-00-912-7682>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6580 inches

Flange Diameter:

Between 0.7450 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4180 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

8

Stator Input Voltage Rating In Volts:

10.2

Stator Input Current Rating:

40.0 milliamperes

Stator Input Electrical Power Rating:

90.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

446.00

Zso Resistance In Ohms:

79.00

Zrs Resistance In Ohms:

548.00

Phase Shift Angle In Deg:

7.800 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

6.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2400 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

1887.00

Plus J Zso Reactance In Ohms:

350.00

Plus J Zrs Reactance In Ohms:

182.00

Shaft Type:

Round single shaft

Transformation Ratio:

2.200 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800