

View Online at <https://aerobasegroup.com/nsn/5990-00-916-9045>

Body Material:

Any acceptable

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 2.3850 inches and 2.4150 inches

Flange Diameter:

1.0620 inches

Flange Thickness:

Between 0.0900 inches and 0.0960 inches

Undercut Diameter:

0.9850 inches

Undercut Width:

0.0450 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.5510 inches single shaft and 0.5750 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

20.0 milliamperes

Stator Input Electrical Power Rating:

300.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

700.00

Zso Resistance In Ohms:

1100.00

Rotor Dc Resistance In Ohms:

350.00

Stator Dc Resistance In Ohms:

650.00

Phase Shift Angle In Deg:

7.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

60.00

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

Between 0.0590 inches and 0.0650 inches

Mounting Surface To Terminal End Distance:

Between 1.8340 inches and 1.8400 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

2800.00

Shaft Slot Depth:

0.0200 inches single shaft and 0.0350 inches single shaft

Plus J Zso Reactance In Ohms:

0.450

Shaft Slot Width:

0.0200 inches single shaft and 0.0350 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Alignment Hole Bolt Circle Diameter:

Between 0.8090 inches and 0.8150 inches

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800