

View Online at <https://aerobasegroup.com/nsn/5990-00-922-4896>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

Between 1.7820 inches and 1.8580 inches

Flange Diameter:

Between 0.7470 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.4910 inches single shaft and 0.5150 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

130.0 milliamperes

Rotor Input Electrical Power Rating:

540.0 milliwatts

Zro Resistance In Ohms:

37.00

Zso Resistance In Ohms:

9.00

Rotor Dc Resistance In Ohms:

27.00

Stator Dc Resistance In Ohms:

10.00

Phase Shift Angle In Deg:

8.500 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

Between 0.0370 inches and 0.0400 inches

Mounting Surface To Terminal End Distance:

Between 1.2910 inches and 1.3430 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

224.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

36.00

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.454 stator to rotor

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800