

View Online at <https://aerobasegroup.com/nsn/5990-00-926-4324>

Body Material:

Steel, stainless

Body Style:

Standard round d

Shoulder Diameter:

Between 1.9850 inches and 1.9900 inches

Pilot Diameter:

0.5950 inches

Second Shoulder Diameter:

Between 1.9985 inches and 1.9995 inches

Second Shoulder Length:

0.1700 inches

Overall Length:

4.2990 inches

Flange Diameter:

Between 2.2490 inches and 2.2500 inches

Flange Thickness:

0.2500 inches

Body Diameter:

1.9900 inches

Shaft Diameter:

0.2403 inches single shaft and 0.2405 inches single shaft

Shaft Length:

0.7190 inches single shaft

Fragility Factor:

Moderately rugged

Maximum Temperature Rise:

35.0 degrees celsius

Body Size:

23

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

60.0

Rotor Input Current Rating:

210.0 milliamperes

Rotor Input Electrical Power Rating:

5.6 watts

Zss Impedance Magnitude In Ohms:

Between 110.00 and 145.00

Zss Impedance Angle In Deg:

Between 10.00 and 17.00

Phase Shift Angle In Deg:

11.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

60.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

160.00

Electrical Error Angular Range In Minutes:

-8.0/+8.0

Spline Tooth Quantity:

22 single shaft

Receiver Error Angular Range In Minutes:

-45.0/+45.0

Torque Gradient Per Angular Deg:

0.120 inch-ounces

Pilot Length:

0.0430 inches

Shoulder Length:

0.2500 inches

Aft Of First Flange Diameter:

1.9400 inches

Mounting Surface To Terminal End Distance:

3.5800 inches

Spline Tooth Diametral Pitch:

96 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a single shaft

Terminal Location:

Rear

Shaft Thread Length:

0.2900 inches single shaft

Shaft Type:

Spline w/threads single shaft

Transformation Ratio:

0.783 stator to rotor

Shaft Thread Size:

0.250 inches single shaft

Test Data Document:

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

Specification Data:

81349-mil-s-20708/56 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800