

View Online at <https://aerobasegroup.com/nsn/5990-00-928-1559>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.1000 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0810 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.5000 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

240.0 milliamperes

Rotor Input Electrical Power Rating:

920.0 milliwatts

Zro Resistance In Ohms:

16.00

Zso Resistance In Ohms:

3.70

Zrs Resistance In Ohms:

22.00

Phase Shift Angle In Deg:

5.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Torque Gradient Per Angular Deg:

5700.0 millimeter-milligrams

Alignment Hole Quantity:

4

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.6000 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

107.00

Shaft Slot Depth:

0.0320 inches single shaft

Plus J Zso Reactance In Ohms:

18.10

Shaft Slot Width:

0.0320 inches single shaft

Plus J Zrs Reactance In Ohms:

8.90

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.454 stator to rotor

Alignment Hole Bolt Circle Diameter:

0.8120 inches

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800