

View Online at <https://aerobasegroup.com/nsn/5990-00-928-5655>

Body Material:

Any acceptable

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

1.7760 inches

Flange Diameter:

Between 1.0590 inches and 1.0620 inches

Flange Thickness:

Between 0.0900 inches and 0.0960 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1190 inches front shaft

Shaft Length:

0.1940 inches front shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

120.0 milliamperes

Rotor Input Electrical Power Rating:

600.0 milliwatts

Zro Resistance In Ohms:

44.00

Zso Resistance In Ohms:

11.70

Zrs Resistance In Ohms:

57.00

Rotor Dc Resistance In Ohms:

Between 16.20 and 19.80

Stator Dc Resistance In Ohms:

Between 8.37 and 10.23

Phase Shift Angle In Deg:

4.300 input to output

Pilot Length:

Between 0.0590 inches and 0.0650 inches

Shoulder Length:

Between 0.0590 inches and 0.0650 inches

Mounting Surface To Terminal End Distance:

1.6200 inches

Shaft Hole Diameter:

0.0200 inches front shaft

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

243.00

Plus J Zso Reactance In Ohms:

40.50

Shaft Tapered End Minor Diameter:

0.1150 inches front shaft

Plus J Zrs Reactance In Ohms:

28.00

Shaft Type:

Round, tapered, hollowed front shaft

Transformation Ratio:

Between 0.440 rotor to stator and 0.468 rotor to stator

Shaft Taper Angle In Deg:

3.0 front shaft

Shaft Taper Length:

0.1310 inches front shaft and 0.1510 inches front shaft

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800