

View Online at <https://aerobasegroup.com/nsn/5990-00-931-4032>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6730 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0630 inches

Undercut Diameter:

0.8450 inches

Undercut Width:

0.0570 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

10

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

36.0 milliamperes

Stator Input Electrical Power Rating:

220.0 milliwatts

Rotor Input Voltage Rating In Volts:

11.8

Frequency In Hertz:

400.0

Rotor Input Current Rating:

91.0 milliamperes

Rotor Input Electrical Power Rating:

230.0 milliwatts

Zro Resistance In Ohms:

34.00

Zso Resistance In Ohms:

212.00

Zrs Resistance In Ohms:

44.00

Rotor Dc Resistance In Ohms:

32.00

Stator Dc Resistance In Ohms:

166.00

Phase Shift Angle In Deg:

14.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

40.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

9.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.00 centimeter-grams

Pilot Length:

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2810 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

119.00

Shaft Slot Depth:

0.0280 inches single shaft

Plus J Zso Reactance In Ohms:

783.00

Shaft Slot Width:

0.0230 inches single shaft

Plus J Zrs Reactance In Ohms:

14.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

7 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800