

View Online at <https://aerobasegroup.com/nsn/5990-00-931-6304>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.3890 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

Between 0.9600 inches and 0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.6860 inches single shaft

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

37.0 milliamperes

Rotor Input Electrical Power Rating:

250.0 milliwatts

Zro Impedance Magnitude In Ohms:

855.00

Zro Impedance Angle In Deg:

77.50

Zso Impedance Magnitude In Ohms:

1185.00

Zso Impedance Angle In Deg:

82.00

Stator Dc Resistance In Ohms:

70.00

Phase Shift Angle In Deg:

9.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

50.00

Electrical Error Angular Range In Minutes:

-18.0/+18.0

Maximum Linear Range In Deg:

-60.0/+60.0

Linearity In Percent:

0.25

Output Voltage Change Per Deg In Volts:

3.4

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7030 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.785 rotor to stator

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800