

View Online at <https://aerobasegroup.com/nsn/5990-00-936-9185>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

0.9750 inches

Pilot Diameter:

0.6250 inches

Overall Length:

2.1800 inches

Flange Diameter:

1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.0000 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.4360 inches single shaft

Body Size:

11

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

70.0 milliamperes

Rotor Input Electrical Power Rating:

1.03 watts

Zro Resistance In Ohms:

950.00

Zso Resistance In Ohms:

10.00

Zrs Resistance In Ohms:

1550.00

Rotor Dc Resistance In Ohms:

700.00

Stator Dc Resistance In Ohms:

10.40

Phase Shift Angle In Deg:

5.600 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 input

Maximum Total Null Voltage Output In Millivolts Per Volt:

17.00

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7340 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

3850.00

Shaft Slot Depth:

0.0350 inches single shaft

Plus J Zso Reactance In Ohms:

36.00

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

420.00

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.1026 rotor to stator

Terminal Type And Quantity:

5 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800