

View Online at <https://aerobasegroup.com/nsn/5990-00-937-7646>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.9380 inches

Flange Diameter:

Between 0.7470 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.7550 inches

Undercut Width:

0.0570 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

115.0 milliamperes

Rotor Input Electrical Power Rating:

540.0 milliwatts

Zro Resistance In Ohms:

54.00

Zso Resistance In Ohms:

12.00

Rotor Dc Resistance In Ohms:

37.00

Stator Dc Resistance In Ohms:

12.00

Phase Shift Angle In Deg:

8.500 input to output

Electrical Error Angular Range In Minutes:

-15.0/+15.0

Actuator Friction Torque At Minus 55 Deg Celsius:

0.6 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

0.3 centimeter-grams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.4070 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

26.00

Shaft Slot Depth:

0.0280 inches single shaft

Plus J Zso Reactance In Ohms:

45.00

Shaft Slot Width:

0.0230 inches single shaft

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800